

Vertical Grinders

Cleco[®]



NEW Cleco® Vertical Grinders

For applications requiring **maximum material removal**, The New Cleco® Vertical Grinder is the solution.

Engineered for heavy-use industrial applications, this product is built to deliver unmatched productivity and maximum material removal.

The Cleco Vertical Grinder is ideally suited for all environments of heavy metal fabrication.

QUALITY

The Cleco® Vertical Grinders are engineered for maximum reliability. All products are 100% tested to ensure the highest quality.

Cleco Vertical Grinders require less maintenance and have more user "up time" to ensure the most from your investment.

SAFETY

All Cleco Vertical Grinders come standard with safety lock throttle lever, industrial governor, and ANSI compliant guards.

Safety is of the utmost importance in any work environment. Cleco Vertical Grinders meet the highest safety standards.

VERSATILITY

Reversible Throttle Handle and Interchangeable 6" (150mm), 7" (180mm), and 9" (230mm) guards.

Cleco Vertical Grinders can be easily and quickly configured for a variety of user preferences and applications.

ERGONOMICS

Reduced weight by up to 1.7 lbs (0.7 Kg) and reduced height by almost 1" (25mm).

Improved ergonomics with Cleco Vertical Grinders enable a more efficient usage and higher operator productivity.



POWER

3HP (2.3Kw) or 4HP (3.1Kw) vane motor are engineered for maximum sustained power.

Cleco Vertical Grinders provide maximum power to generate maximum material removal.



DURABILITY

Streamlined one piece all metal housing and handles are engineered for ultimate ruggedness.

Cleco Vertical Grinders can withstand the most abusive environments.



PRODUCT SPECIFICATIONS



MODEL	EXTERNAL THREAD	ABRASIVE CAPACITY	MAX. FREE SPEED	POWER		HEIGHT		WEIGHT		AIR INLET
			rpm	hp	Kw	in	mm	lbs	kg	

3 HP (2.3Kw) SERIES

3060AVL-06	5/8" 11 External Thread	6" (150mm) Type 11	6,000	3.1	2.3	6.9	175.3	10.2	4.6	1/2"
3060AVL-07	5/8" 11 External Thread	7" (180mm) Type 27	6,000	3.1	2.3	6.9	175.3	9.7	4.4	1/2"
3060AVL-09	5/8" 11 External Thread	9" (230mm) Type 27	6,000	3.1	2.3	6.9	175.3	10.4	4.7	1/2"

4 HP (3.1Kw) SERIES

4060AVL-06	5/8" 11 External Thread	6" (150mm) Type 11	6,000	4.1	3.1	8.2	207.9	11.6	5.3	1/2"
4060AVL-07	5/8" 11 External Thread	7" (180mm) Type 27	6,000	4.1	3.1	8.2	207.9	11.1	5.0	1/2"
4060AVL-09	5/8" 11 External Thread	9" (230mm) Type 27	6,000	4.1	3.1	8.2	207.9	11.8	5.4	1/2"

3HP (2.3Kw)



4HP (3.1Kw)



GUARD Options



6" (150mm)

7" (180mm)

9" (230mm)

United States
Apex Tool Group
670 Industrial Drive
Lexington, SC 29072
Phone: +1 800 845 5629
Fax: +1 803 358 7681
www.apexpowertools.com

Germany
Apex Tool Group
GmbH & Co.
Industriestraße 1
73463 Westhausen
Germany
Phone: +49 (0) 73 63 81 0
Fax: +49 (0) 73 63 81 222
www.apexpowertools.eu

China
Apex Power Tool Trading
(Shanghai) Co., Ltd
Building A8, No. 38
Dongsheng Road
Pudong, Shanghai
China 201201
Phone: +86 21 60880320
Fax: +86 21 608803313
www.aptpowertools.com.cn

India
Apex Power Tools India
Private Limited
Gala No. 1, Plot No. 5
S. No. 234, 235 & 245
Indialand Global Industrial Park
Taluka-Mulsi, Phase I
Hinjawadi, Pune 411057
Maharashtra, India
Phone: +91 20 66761111

Brazil
Apex Tool Group
Ind. Com. Ferram. Ltda
Av. Liberdade, 4055
Zona Industrial Iporanga
Sorocaba, São Paulo
CEP# 18087-170
Brazil
Tel: +55 15 2383929
Fax: +55 15 2383260

Mexico
Apex Tool Group Manufacturing
México S. de RL de CV
Vialidad El Pueblito #103
Parque Industrial Querétaro
Querétaro, QRO CP# 76220
Mexico
Tel: +52 (442) 211 3800
Fax: +52 (800) 685 5560

